

Tip 4/2 Thermoplastic Hose



Applications

Waterblast : Heat exchanger tube cleaning

Hydraulics : Pressure test equipment (valves, tooling and control panels), hydraulic tools (instrumentation packages for gauges, control of service equipment, hydraulic jacks, hydraulic tools)

Inner Core : Polyoxymethylene (POM)
 Pressure Support : 2 layers of high-tensile steel wire
 Outer Cover : Polyamide (PA)
 Colour : Green, other colours optional.
 Temperature : [-30 °C to +60 °C]

Lenght (m)	Part No
5	00.70.0000
10	00.70.0050

Inner Diameter Ø mm	Outer Diameter Ø mm	Working Pressure * Bar	Burst Pressure Bar	Bend Radius mm	Weight kg/m	Inner Diameter of Insert Ø mm	Outer Cover Material	Outer Cover Diameter Ø mm
4	8	1200	3000	75	0.110	2.5	Carbon Steel	10

* Safety factor between burst pressure and working pressure as well as test pressure depends on operating conditions. For gaseous media a safety factor of 1:6 is to be applied and the outer cover is to be pricked. The indicated working pressure refers to the hos only. Depending on the used fitting the permitted working pressure of a hose assembly can be less.

Fitting
 Fitting Type : Male
 Thread : M7
 Material : Carbon Steel

